

**ANALOG  
960H**



# **CCD238 MINI CAMERA TYPE "BULLET"**

ITEM NUMBER: 063VT238  
MODEL: MC270J

Mini colour CCTV camera in "bullet" style, Sony  
CCD, weatherproof

## **Key Features**

Mini Colour Camera  
1/3" Sony© Super HAD CCD II  
Image Sensor  
650TV Lines, 960H format  
3.6mm lens  
0.1 Lux, F2.0  
For indoor and outdoor use

CCTV Systems  
Distribution Ireland  
Unit 6A Aran Centre  
Blessington Business Park  
Blessington  
Co. Wicklow  
Ireland

Phone: +353 1 443 3386  
Web: [www.cctvdi.com](http://www.cctvdi.com)  
Email: [sales@cctvdi.com](mailto:sales@cctvdi.com)

**cctvdi.com**  
HD CCTV for Less!

## Description

Miniature CCTV colour camera in "bullet" format.

The image sensor is a 1/3" Sony© Super HAD CCD II 960H (ICX811AKA model) and Effio-E DSP (CXD4140AGG model) with a resolution of 650 TVL. Optical fixed lens with 3.6mm focal length with a diagonal field of view of 79°. Minimum illumination of 0.1 Lux for proper operation in low light conditions.

BNC video connection to connect to standard analogue CCTV systems (960H / D1 / CIF).

Protective weatherproof metal housing, suitable for indoor and outdoor use.

## Scope of Delivery

Miniature Camera CCD238  
Bracket  
Power adapter 12V DC  
Instructions

## Technical Specifications

Image Sensor	1/3" Sony© Super HAD II CCD, 960H (ICX811AKA model)
DSP	Effio-E (CXD4140GG model)
Horizontal Resolution	650TV Lines
Video Output	1x BNC 1 Vp-p 75 $\Omega$ (CVBS)
Minimum Illumination	0.1 Lux / F2.0
S/N ratio	>52dB
Lens	Optical fixed Lens 3.6mm (79° degrees field of view)
Image Enhancement Features	AGC (Automatic Gain Control), BLC (Back Light Compensation), HLC (High Light Compensation), ATW (Auto Trace White)
Application	Indoors and Outdoors (weatherproof), bracket included
Power Supply	DC 12V, 75mA, power supply included
Operating Temperature	-10° C ~ +50° C
Dimensions	75(L) x 23( $\emptyset$ ) mm
Weight	40g