



DCG152HD 4 IN 1 VARIFOCAL CAMERA 2.1 MEGA PIXEL FULL HD

ITEM NUMBER: 066VT152GHD
MODEL: DM957VI-F4N1

4 in 1 full HD CCTV varifocal dome camera
1080p 2.1 Mega Pixel, supports HD-CVI, HD-TVI,
AHD and 960H analogue, 40m (131ft) night vision
– F4IN1

cctvdi.com
HD CCTV for Less!

Key Features

Compact Colour Dome Camera
4 in 1, supports all video standards: HD-CVI, HD-TVI, AHD, 960H analogue
1/2.7" CMOS PS5220
2.1 Megapixel Video Board
1080p HD resolution
2.8 to 12mm varifocal lens
3 Array Infrared LEDs for up to 40m (131ft) night vision
3 Axis design
OSD menu controlled via DVR menu

CCTV Systems
Distribution Ireland
Unit 6A Aran Centre
Blessington Business Park
Blessington
Co. Wicklow
Ireland

Phone: +353 1 443 3386
Web: www.cctvdi.com
Email: sales@cctvdi.com

Description

CCTV colour varifocal dome camera with 4 in 1 technology – supports HD-CVI, HD-TVI, AHD of up to 2.1 Mega Pixel 1080p HD resolution and analogue 960H (CVBS). The camera is equipped with infrared night vision and suitable for outdoor and indoor use.

The camera provides high definition video via coaxial cable or UTP and also a standard analogue CVBS video signal. The 1/2.7" 2.1 Megapixel video sensor (model PS5220) together with the DSP (model V30) chipset provides a resolution of full HD 1080p at 25fps (frames per second) in brilliant HD quality (all standards supported: HD-CVI, HD-TVI, AHD), as well as a standard 960H analogue CVBS signal for testing purposes. That means the camera operates with modern high definition systems as well as standard analogue CCTV installations.

Varifocal optical lens with 2.8 to 12mm focal length with a diagonal field of view of 94° to 25°.

3 Array infrared LEDs are activated automatically in low light conditions, providing a sharp image at 0lux (total darkness) to a maximum distance of 40m (131ft).

The integrated automatic IR CUT filter provides a sharp image with realistic colours during daytime operation.

OSD menu of the DSP can be accessed directly from the DVR (e.g. our Dahua DVR range) and this allows to configure the camera and adjust the most important parameters:

- AE Shutter, automatic exposure control to optimise the input light received
- 2D-NR system, digital noise reduction without loss of focus
- AWB, automatic white balance for a true colours

The advantage of this camera in connection with our Dahua X-Security DVR range is, that you can control the OSD via the DVR without the need of any additional cabling (only available in HD operation).

Video connection via standard BNC connector, switchable between HD-CVI, HD-TVI, AHD and analogue CVBS (PAL), 960H (recommended for testing purposes).

Solid housing made of aluminium, weatherproof according to IP66 specifications, can be used outdoors and indoors. It has a three axis design bracket that allows easy and accurate adjustment of the viewing angle with wall or ceiling installation. Bracket is included.

Scope of Delivery

CCTV 4 in 1 camera DCG152HD

Fittings

Alan Key

Power adapter 12V DC

Manual

Technical Specifications

Image Sensor	1/2.7" 2.1 Megapixel model PS5220
DSP	V30
Resolution	HD 1080p (1920x1080 pixels) at 25fps / 960H analogue CVBS (for testing purposes)
Video Output	1x BNC for HDCVI, HDTVI, AHD and CVBS (switchable)
Minimum Illumination	0 Lux (IR on)
Night vision	3 Array Infrared LEDs, up to 40m (131ft) infrared night vision with automatic IR CUT filter
Lens	2.8 to 12mm optical varifocal lens, 94° to 25° field of view
Image Enhancement and OSD features	Day / Night IR-CUT (ICR), DWDR, 2D-NR, AE, AWB, AGC, OSD menu accessible via menu of HD DVRs
Weatherproof and Dustproof rating	IP66 for outdoor and indoor use
Housing	solid metal housing made of aluminium, colour: dark grey
Power Supply	DC 12V, 450mA, Power Supply included
Operating Temperature	-10° C ~ +60° C
Dimensions	95(H) x 120 (Ø) mm
Weight	500g
Camera Type	4 in 1 1080p ECO Range (F4N1)