

# NVW2007HD

## 4 IN 1 BULLET CAMERA, 2MP

item number: 0622007HD

- 1/2,7" CMOS, 2 MP
- Digital resolution: 1080P (1920x1080)
- 25/30 frames per second
- 4 in 1 output (switch): HDCVI / HDTVI / AHD / CVBS 960H
- Smart IR: 20 m (24 leds)
- 3,6 mm fixed lens
- OSD via coaxial (only on CVI, TVI, AHD mode; 300 m range)
- AWB, AGC, 2D-NR, digital WDR
- IP66
- 3AXIS bracket included
- Power supply is included



### TECHNICAL SPECIFICATION

CAMERA	
Image sensor	1/2,7" CMOS, 2 MP
Effective pixels	1936 (H) x 1096 (V)
Signal system	PAL/NTSC
Synchronization	Internal
IR illumination	Smart IR: 24 led, 20 m
Minimum illumination	0,1 lux F1.2 color (AGC On) / 0,01 lux F1.2 B/N (AGC On)
Signal to noise ratio	39 dB (AGC Off)
Video output	HDCVI / HDTVI / AHD / CVBS 960H (960H CVBS for testing purposes only)
LENS	
Lens	3,6 mm
VIDEO	
Resolution	1920x1080 (CVI, TVI, AHD), 1280x576, 1280x480 (CVBS)
Frames per second	25/30 fps
FUNCTIONS	
Day/night mode	Ext, Auto, Color, B/W
OSD	Menu via coaxial, up to 300 meters
Shutter	Auto
White balance	Auto / Manual
Gain control	Auto
Digital WDR	On / Off
Noise reduction	2D
ELECTRICAL	
Power supply	12V DC (±10%), 250 mA
Consumption	<3W
Storage temperature	-20°C ~ +60°C
Working temperature	-10°C ~ +60°C
RH	<90% (without condensation)
Protection	IP66
GENERAL	
Dimensions	66,9 x 59,4 x 160,7 mm
Weight	190 g