



KEY FEATURES

- HDTVI dome Starlight with Smart IR of 40m for outdoors
- 2MP CMOS
- HDTVI output
- 2.8 ~ 12mm (103°~32.1°) motorized lens with autofocus
- ICR
- OSD, ATW/MWB, AGC, BLC, HLC, real WDR 120dB, 3D-DNR, mirror mode, brightness and sharpness adjustment, motion detection and privacy mask
- IP67
- 3AXIS
- 12V DC

FEATURES

- 2 MP CMOS sensor
- Digital resolution: 1080P (1920x1080)@25 fps
- HDTVI video output
- 0.005 lux F1.8 color / 0 lux IR On
- Removable mechanical filter
- Smart IR: EXIR 2.0 technology, 40 meters (**131ft**)
- 2.8 ~ 12mm motorized lens (103°~32,1°)
- OSD menu via coaxial
- ATW/MWB, AGC
- BLC, HLC, real WDR 120dB
- 3D-DNR
- Motion detection: 4 programmable zones
- 4 programmable privacy masks
- Mirror mode, brightness and sharpness adjustment
- Working temperature -40°C~+60°C
- RH: ≤90% (without condensation)
- IP67
- Metal case
- Power supply: 12V DC (±25%)
- Consumption: Max. 8W
- Dimensions: 134.3 x 123.9 x 111.4 mm
- Weight: 750 g
- 3AXIS: wall and ceiling installation