



HDCVI™ HDTVI AHD CVBS
SMP

KEY FEATURES

- 4 in 1 dome PRO series with Smart IR of 40 m for outdoors
- 5MP CMOS
- 4 in 1 output (HDCVI / HDTVI / AHD / 960H)
- 2,7 ~ 13,5 mm mototrizied lens (95,7°~29,1°)
- ICR filter
- OSD, ATW, MWB, AGC, BLC, digital WDR, 2D-DNR, brightness, sharpness, mirror
- IP67
- 3AXIS
- 12V DC

FEATURES

- 5 MP CMOS sensor
- Digital resolution: 5MP@20 fps, 4MP@25/30 fps 1080P@25/30 fps
- 4 in 1 video output (switch): HDCVI / HDTVI / AHD / 960H
- 0,01 lux F1.2 color / 0 lux IR On
- Removable mechanical filter
- Smart IR: EXIR 2.0 technology, 40 meters
- 2,7 ~ 13,5 mm motorized lens (95,7°~29,1°)
- OSD menu via coaxial
- ATW/MWB
- AGC: Automatic gain control
- Backlight compensation: BLC, WDR digital
- 2D-DNR: 2D
- Brightness and sharpness adjustment
- Mirror mode
- Working temperature -40°C~+60°C
- RH: ≤90% (without condensation)
- IP67
- Metal case
- Power supply: 12V DC (±25%)
- Consumption: 6,3W max
- Dimensions: 123,86 x 134,3 x 110,11 mm
- Weight: 580 g
- 3AXIS: wall and ceiling installation