

XS-XVR6104S-1AI

DVR 5n1 X-Security

4 CH

HDTVI/HDCVI/AHD/CVBS(5Mpx) + 2

IP(6Mpx)

Audio over coaxial

5M-N (10FPS) Recording Resolution

1 CH facial recognition

2 CH Human and vehicle recognition



X-Security

XVR 5n1

4 CH video HDTVI/HDCVI/AHD/CVBS / 4+2 IP / 1 CH audio

H.265Pro+/H.265Pro/H.264+/H.264

Recording resolution 5M-N (10FPS) or 4M-N/1080p (15FPS) or 1080N/720P (25/30FPS) [%VAR%]

PTZ Control (RS485/Coaxial)

Audio over coaxial

HDMI Full HD, VGA & CVBS Outputs

2 CH Perimeter Protection

1 CH comparison of face

Human and Vehicle Recognition (Available for 4 CH coaxial video)

Mouse

2 USB Ports

Space for 1 HDD

Compact size

cctvdi  com

📍 Unit 6A Aran Centre, Blessington Business Park
Blessington, Co. Wicklow, W91 VN27 Ireland

☎ +353 1 4433386 ✉ sales@cctvdi.com

🌐 www.cctvdi.com

Specifications

| | |
|------------------------------|--|
| Brand | X-Security |
| Video format | HDTVI / HDCVI / AHD / CVBS / IP |
| Video inputs | 4 Channels BNC (HDTVI / HDCVI / AHD / CVBS) |
| Hybrid configuration | Up to 6 IP Channels (6Mpx), replacing all the BNC channels |
| Video outputs | 1 HDMI 1080p, 1 VGA |
| Video / audio compression | H.265+/H.265/H.264+/H.264 |
| Display resolution | 1920x1080, 1280x1024, 1280x720 |
| Total bandwidth | 32 Mbps |
| Recording resolution | 5 M-N, 4 M-N,1080p, 1080N, 720p, 960H, D1, CIF |
| Main Stream coding | 5M-N(10 FPS); 4M-N/1080p(15 FPS); 1080N / 720p / 960H / D1 / CIF (25/30 FPS) |
| Extra Stream coding | D1 / CIF (1-15 FPS) |
| Simultaneous multifunction | Pentaplex: Live, Recording, Playback, Backup and Remote Access |
| Audio inputs | 1 Channel RCA |
| Audio outputs | 1 Channel RCA |
| Bidirectional audio | Reusing the audio input/output |
| Alarms IN/OUT | Does not have |
| Video analysis | IVS: Tripwire Area intrusion Abandoned object Face detection |
| Facial recognition | 1 live analogue face comparison channel |
| Intelligent motion detection | Up to 4 channels capable of classifying targets amongst humans and vehicles |
| Recording method | Manual, programmed, motion detection, alarm |
| Backup | USB / Network |
| Internal memory | 1 SATA HDD 3.5" of up to 16 TB (not included) |
| Communication | RS485 (PTZ) /2 x USB (Mouse and backup) / RJ45 10/100 (Ethernet) |
| Remote access | Web browser (ActiveX), mobile phone application or PSS software |
| Power | DC 12V / 1.5A |
| Dimensions / Weight | 47.6 (H) x 260 (W) x 237.5 (D) mm / 1 Kg |

cctvdi@com

Unit 6A Aran Centre, Blessington Business Park
Blessington, Co. Wicklow, W91 VN27 Ireland

+353 1 4433386 sales@cctvdi.com

www.cctvdi.com