

# XS-XVR6116S-2AI

DVR 5n1 X-Security  
16 CH HDTV/HDCVI/AHD/CVBS  
(5Mpx) + 8 IP (6Mpx)  
Audio over coaxial  
5M-N (10FPS) Recording Resolution  
2 CH facial recognition  
16 CH Human and vehicle recognition



X-Security  
DVR 5n1  
16 CH video HDTV/HDCVI/AHD/CVBS / 16+8 IP / 16 CH audio  
H.265+/H.265/H.264+/H.264  
Resolución 5M-N (10FPS) o 4M-N/1080p (15FPS) o 1080N/720P (25/30FPS)  
PTZ Control (RS485/Coaxial)  
Audio over coaxial  
HDMI Full HD, VGA & CVBS Outputs  
2 CH comparison of face  
Human and Vehicle Recognition (Available for 16 CH coaxial video)  
Mouse  
2 USB Ports  
Space for 1 HDD  
Compact size

cctvdi@com

Unit 6A Aran Centre, Blessington Business Park  
Blessington, Co. Wicklow, W91 VN27 Ireland

+353 1 4433386 sales@cctvdi.com

www.cctvdi.com

# Specifications

Brand	X-Security
Video format	HDTVI / HDCVI / AHD / CVBS / IP
Video inputs	16 Channels BNC (HDTVI / HDCVI / AHD / CVBS)
Hybrid configuration	Up to 24 IP Channels (6Mpx), replacing all the BNC channels
Video outputs	1 HDMI Full HD, 1 VGA
Video / audio compression	H.265+/H.265/H.264+/H.264
Display resolution	1920x1080, 1280x1024, 1280x720
Total bandwidth	128 Mbps
Recording resolution	5 M-N, 4 M-N,1080p, 1080N, 720p, 960H, D1, CIF
Coding	All channel: 5M-N(10 FPS); 4M-N/1080p(15 FPS); 1080N / 720p / 960H / D1 / CIF (25/30 FPS)
Dual-Stream encoding	D1 / CIF (1-15 FPS)
Simultaneous multifunction	Pentaplex: Live, Recording, Playback, Backup and Remote Access
Audio inputs	8 BNC, 1 RCA Channel
Audio outputs	1 Channel RCA
Bidirectional audio	Reusing the audio input/output
Alarms	No
Video analysis	IVS: Tripwire   Area intrusion   Abandoned object   Face detection IP Mode, Face Recognition and IVS cannot be enabled at the same time
Facial recognition	Up to 2 analog channels for live face comparison
Intelligent motion detection	Up to 16 channels capable of classifying targets amongst humans and vehicles
Recording method	Manual, programmed, motion detection, alarm
Backup	USB / Network
Internal memory	1 SATA HDD 3.5" of up to 10 TB (not included)
Communication	RS485 (PTZ) /2 x USB (Mouse and backup) / RJ45 10/100 (Ethernet)
Remote access	Web browser (ActiveX), mobile phone application or PSS software
Power	DC 12V / 2A
Dimensions / Weight	47.6 (H) x 260 (W) x 237.4 (D) mm / 1.17 Kg

**cctvdi@com**

Unit 6A Aran Centre, Blessington Business Park  
Blessington, Co. Wicklow, W91 VN27 Ireland

+353 1 4433386 ✉ sales@cctvdi.com

www.cctvdi.com